



SPECIFICATIONS

SS-240SN-E260* CC DRIVER

Model: SS-240SN-E260*

Power: 240W

Rev.: V04

Release date: 2025-04-07



SS-240SN-E260*Series LED DRIVER

Features

- Efficiency up to 95%
- Isolated dimming: 0-10V,PWM,Resistor
- Dim-to-Off without afterglow
- Surge protection: CM: 6kV, DM: 6kV
- AUX Power: 12V/0.2A
- Standby Power<1.5W
- IP65
- Type HL, Suitable for hazardous locations
- Protections: SCP/OTP/UVP
- Warranty: 5 years



IP65

Description

SS-240SN-E260* Series are 240W round non-isolated constant current LED Driver. Three powers of 240W-200W- 150W can be obtained through the DIP switch . It is specially designed for commercial lightings with isolation dimming function. Ultra high efficiency, compact housing design and fully potted thermally conductive silicon ensure LED Driver cooling and waterproof , high reliability, high cost performance and many more.

Applications:

High bay lighting, High pole lightings.

Model List

Model	AC Input Range	Max. Pout	Vout Range	Recommended Voltage	Iout	THD (Typ.)	PF (Typ.)	Eff. (Typ.)	Max.Tc
SS-240SN-E260*	108-380Vac	240W	180-260V	200V-260V	0.55-1.2A	7%	0.98	95%	90℃

Note:

1.Default Tested:at220Vac,fullload, Ta 25°C.

2.The performance of the LED Driver can be guaranteed within the full power Vo range.The voltage lower than full power Vo range, it is need to test the performance with the LED module.

SS-240SN-E260*Series LED DRIVER

“*” Means Additional Function

“*”	AUX 12V suffix:H)	Dimming off 0-10V/PWM/Resistor	Adjust power (Single DIP)	Adjust power/color temperature (Double DIP)	Remark
BHB	✓	✓	✓		
BHD	✓	✓		✓	


Input Characteristics

Parameter	Min.	Typ.	Max.	Remark
Rated AC Input Range	120Vac		347Vac	
AC Input Range	108Vac		380Vac	Ref. derating curve
Input Frequency Range	47Hz	50/60Hz	63Hz	
Max Input Current			3.0A	120Vac, Full load
Max Input Power			275W	120Vac, Full load
Max Inrush Current(120Vac)			60A	Cold start
Max Inrush Current(220Vac)			100A	Cold start
Max Inrush Current(347Vac)			130A	Cold start
Standby Power			1.5W	220Vac/50Hz, Dim to off or Enable STB
Power Factor	0.95	0.98		220Vac/50Hz, Full load
	0.90			120-347Vac/50Hz, 70-100% load
THD		7%	15%	220Vac/50Hz, Full load
			20%	120-347Vac/50Hz, 70-100% load

SS-240SN-E260*Series LED DRIVER


Dip Switches:

BHD Dip Switch to adjust output power
+ Dip Switch to adjust color temperature



240W(A)-200W(B)-150W(C)
CW White light NW Neutral light WW Warm light

BHB Dip Switch to adjust output power



240W(A)-200W(B)-150W(C)
CW NW WW No special meaning

Note: To adjust the output power and color temperature, you need to operate after AC OFF.

SS-240SN-E260*Series LED DRIVER

Output Characteristics

Parameter	Min.	Typ.	Max.	Remark
O/P Voltage Range	180V		260V	
Rated O/P Voltage	200V		260V	$P_o = V_o \cdot I_o = 240W$, Full load
Rated O/P Current	0.92A		1.2A	1.2A for 200V, 0.92A for 260V
Adj. O/P Current (AOC) Range	0.84A		1.2A	A
	0.75A		1.1A	B
	0.55A		0.85A	C
No Load Voltage			310V	
Efficiency @120Vac	90.0%	92.0%		O/P 260V/0.92A
Efficiency @220Vac	92.0%	95.0%		O/P 260V/0.92A
Efficiency @347Vac	92.0%	95.0%		O/P 260V/0.92A
O/P Current Tolerance	-5%		+5%	
O/P Current Ripple(PK-AV)		10%	15%	Full load
Start-up Current Overshoot			10%	Full load
Start-up Time			1.0S	120Vac, Full load
			1.0S	347Vac, Full load
Line Regulation	-1%		+1%	Full load
Load Regulation	-2%		+2%	
Temperature Coefficient	-0.03%/°C		+0.03%/°C	T _c : 0°C~90°C
OTP	90°C	100°C	110°C	Drop current when OTP, and it can be automatically restored after the abnormality is removed.
Short Circuit Protection				Driver will not be damaged, Hiccup mode

SS-240SN-E260*Series LED DRIVER

Other Characteristics

Parameter		Min.	Typ.	Max.	Remark
Aux Power	O/P Voltage	11V	12V	13.2V	Maximum no-load voltage 14.5V
	O/P Current			200mA	O/P:150mA at -40°C
0-10V Dimming	Dim Voltage	0V		12V	DIM+ source current 100uA.
	Dim Range	13%loset		100%loset	Dimming prohibits reverse connection
	Rec.Dim Range	0V		10V	
PWM Dimming	PWM High	9.8V		10.2V	DIM+ source current 100uA.
	PWM Low	0V		0.3V	Dimming prohibits reverse connection
	Frequency	1KHz		2KHz	
	PWM Duty	0%		100%	Dimming can be off.
Resistor Dimming	Resistance	0Kohm		100Kohm	Dimming can be off.
	Dim Range	13%loset		100%loset	DIM+ source current 100uA.
Dim to Off (Optional)	Dim off	0.7V	0.8V	0.97V	When DIM- and Vaux- are shared with single wire output, the dimming off point and dimming on point are tested under no load of the auxiliary power.
	Dim on	0.97V	1.1V	1.2V	
Life Time(Tc≤85°C)		50,000 hours			
MTBF		198,000 hours			347Vac,Full load, Ta=25°C (MIL-HDBK-217F)
IP Grade		IP65			
Tc		90°C			
Warranty		5 years			Tc: 85°C
Net Weight		890g			
Dimension		Φ136mm*62.5mm			D x H

NOTE: All the parameters above are tested Ta 25°C and LED load, unless specified.

SS-240SN-E260*Series LED DRIVER

Environmental Requirements

Parameter	Min.	Typ.	Max.	Remark
Operating Temperature(Tcase)	-40°C	25°C	+90°C	
Storage Temperature	-40°C	25°C	+90°C	
Operation Humidity	10%RH		90%RH	
Storage Humidity	5%RH		95%RH	
Altitude	-65m		4000m	

Safety and EMI/EMS Standards

Certification	Standard	Status	Remark
UL/cUL	UL8750	✓	
TUV	EN 61347-2-13:2014/A1:2017 EN 61347-1:2015 EN 62493:2015		
RCM	AS/NZS61347.2.13		
CCC	GB 19510.14-2009		
CE	EN 61347-2-13:2014 EN61347-1:2008+A1:2011+A2:2013		

EMI/EMS	Criterion	Remark
Conduction Emission	FCC Part15: Subpart A; ANSI 63.4:2014	Class A
Radiation Emission	FCC Part15: Subpart A; ANSI 63.4:2014	Class A
Harmonic Current Emissions	IEC/EN 61000-3-2	Class C
Surge	IEC/EN61000-4-5	DM: 6kV,CM: 6kV,Criterion B
	ANSI/C82.77-5-2017	DM: 6kV,CM: 6kV,Criterion B
Ring Wave	IEC/EN 61000-4-12;ANSI/C82.77-5-2017	DM: 6kV,CM: 6kV,Criterion B

SS-240SN-E260*Series LED DRIVER


Safety Test Items

Safety Test Items	Technical Indicators		Remark
Insulation Requirements	UL Insulation Requirements	TUV Insulation Requirements	
Input-Case	1600Vac	/	Basic insulation
Input-Dim	1600Vac	/	Reinforced insulation
O/P-Dim	1600Vac	/	Reinforced insulation
Dim-Case	500Vac	/	Basic insulation
Insulation Resistance	$\geq 10\text{M}\Omega$		Input-Dim, Test voltage: 500Vdc
Ground Resistance	$\leq 0.1\Omega$		25A/1min
Leakage Current	$\leq 0.75\text{mA}$		347Vac

- NOTE:
1. SOSEN warrants the LED Driver itself complies with EMC standard. However, LED Driver's EMC should be re-checked when integrated into lighting systems due to unexpected interference of components.
 2. Please short (ACL and ACN), (V+ and V-), (Dim+ and Dim - and Vaux+ and Vaux-)when Hi-pot test.
 3. During the HI-POT, the built-in GDT and the ground connection terminal wire shall be disconnected.

Performance Curves

Input Inrush Current




Vin	Ipeak	T(@10% of Ipeak)	T(@50% of Ipeak)
120Vac	60A	542uS	
220Vac	100A		250uS
347Vac	130A	582uS	


SS-240SN-E260*Series LED DRIVER

Performance Curves

Output Voltage Vs. Output Current(Dim/AOC Window)




Efficiency Vs. Output Voltage(Vin=120Vac)




SS-240SN-E260*Series LED DRIVER

Performance Curves

Efficiency Vs. Output Voltage (Vin=220Vac)




Efficiency Vs. Output Voltage(Vin=347Vac)




SS-240SN-E260*Series LED DRIVER

Performance Curves

Power Factor Vs. Output Power




THD Vs. Output Power




SS-240SN-E260*Series LED DRIVER

Performance Curves


Output Power Vs. Input Voltage




Output Power Vs. Case Temperature



Output Power Vs. Dimming




Lifetime Vs. Case Temperature



SS-240SN-E260*Series LED DRIVER

Mechanical Characteristic



AC Input Cable(Exposed Length 300±10mm):

UL model: STW,3*18AWG ,O.D:9.4mm,Black:ACL, White:ACN, Green: Terminate

DC Output Cable(Exposed Length 300±10mm):


UL model(BHB model): SJTW,2*18AWG, O.D:7.3mm, Red: V+, Black: V-
UL model(BHD model): SJTW,3*18AWG, O.D:7.8mm, Red: LED+, Blue: Warm light(LED1-), Black: White light(LED2-)

DIM/AUX Cable(Exposed Length 220±10mm):

UL Model:
UL 21996 3*22AWG , O.D: 4.9mm Purple: DIM+, Pink: DIM-/Vaux-, Black/White: Vaux+
UL 21996 2*22AWG , O.D: 4.7mm Purple: DIM+, Pink: DIM-

Name Description	Standard code	mm(In.)
Input line hole	A	13(0.51)
Mounting Screw Diameter	4-B	Φ7.0(0.28)
Case Diameter	D	Φ136(5.35)
Height	H	62.5(2.46)
Ring Hole	Z	M10*1.5 (Depth 18mm) G1/2 (Depth 18mm)
Ring Fixed Hole	R	M4*0.7
Mount Size	W	113(4.45)
TC Point Position	X	10(0.39)
TC Point Position	Y	33(1.3)

Note
1,Please follow the "LED Driver User Manual" obtained from SOSEN's official website for assembly.
2,AC Input Cable,DC O/P Cable,DIM/AUX Power/Programming Cable:
Peeled length of cable:43±5mm, Tinned length of wire:10±2mm



SS-240SN-E260*Series LED DRIVER



Assembly Tips

1. Highly recommended to seal the adjustable hole with silicon glue(#704 preferred) after adjusting the Driver's output current. Avoid permanent damage to adjust the potentiometer with suitable strength.
2. Dimming or AUX Power tinned connectors should be capped if not used to avoid dimming or AUX Power parts damage from external signals.
3. Safety space between aluminum base and LED coppers >5mm.
4. Safety space/coppers between LED+ and LED- >1.8mm.
5. Minimize the copper area on the aluminum PCB to reduce parasitic capacitance and leakage current.
6. It is recommended to design LED beads in parallel first and then in series.
7. The insulation level of LED light panels should meet the reliability design requirements.
8. For other precautions, please refer to the "LED Driver User Manual".

Package

- Outside carton dimension: L×W×H =580mm×433mm×210mm;
- 8PCS/Carton;
- Net weight/Piece: 0.89kg;Gross weight/Carton: 9.11kg;
- Please refer to the product name, model number, manufacturer identification, QC PASS, manufacturing date on the package.

Transportation

Packaging is designed suitable for transportation by trucks, vessels and flights. The products should be avoided direct sunlight and rain, loaded/unloaded with caution.

Storage

The product storage meets the standard of the GB 3873—83.

Products should be rechecked if stored for over 1 year before installation.

RoHS

Products comply with RoHS Directive (2011/65/EU) and amendment 2015/863/EU.

Revision History

Version	Description of Update	Updated Date	Remark
V00	Original release	2023/05/25	
V01	Update Remark Of Dim To Off	2023/07/13	
V02	Update Additional Function	2023/08/22	
V03	Update Lifetime	2023/11/17	
V04	Update Characteristic Curve	2025/04/07	