

SPECIFICATIONS

SS-120NH-E260D


CC DRIVER

Model: SS-120NH-E260D

Power: 120W

Rev.: V04

Release date: 2025-04-22



SS-120NH-E260D LED DRIVER

Features

- Efficiency up to 95%
- DALI-2
- Isolated Dim-to-off
- Standby power<0.5W
- Protections: SCP/OTP
- Surge protection: CM: 6kV, DM: 6kV
- Warranty: 5 years



Description

SS-120NH-E260D are 120W non-isolated constant current LED Driver with 90-305VAC. It has DIM to Off, high efficiency, compact housing ,fully potted , high reliability, high cost performance and other advantages.

Applications:

Wall washers, Linear high bay light, Flood lighting, Wall lamp

Model List

Model	AC Input Range	Max. Pout	Vout Range	Recommended Voltage	Iout	THD (Typ.)	PF (Typ.)	Eff. (Typ.)	Max.Tc
SS-120NH-E260D	90-305Vac	120W	180-260V	200V-260V	0.42-0.6A	8%	0.97	95%	90°C

Note:

1.Default Tested: at 220Vac, full load, Ta 25°C.

2.The performance of the LED Driver can be guaranteed within the full power Vo range.The voltage lower than full power Vo range, it is need to test the performance with the LED module;

SS-120NH-E260D LED DRIVER

Input Characteristics

Parameter	Min.	Typ.	Max.	Remark
Rated AC Input Range	100Vac		277Vac	Ref. derating curve
AC Input Range	90Vac		305Vac	Ref. derating curve
Input Frequency Range	47Hz	50/60Hz	63Hz	
Max Input Current			1.22A	120Vac, Full load
Max Input Power			147W	120Vac, Full load
Max Inrush Current(120Vac)			60A	Cold start
Max Inrush Current(220Vac)			100A	Cold start
Max Inrush Current(277Vac)			130A	Cold start
Standby Power			0.5W	220Vac/50Hz, DALI Dim-to-off
Power Factor	0.95	0.97		220Vac/50Hz, Full load
	0.90			100-277Vac/50Hz, 70%-100% load
THD		8%	10%	220Vac/50Hz, Full load
			20%	100-277Vac/50Hz,70%-100% load

SS-120NH-E260D LED DRIVER

Output Characteristics

Parameter	Min.	Typ.	Max.	Remark
O/P Voltage Range	180V		260V	Power derated @180-200V
Rated O/P Voltage	200V		260V	$P_o = V_o \cdot I_o = 120W$, Full load
Rated O/P Current	0.46A		0.6A	0.6A for 200V, 0.46A for 260V
Adj. O/P Current (AOC) Range	0.42A		0.6A	
No Load Voltage			310V	
Efficiency @120Vac	89.0%	91.0%		Output 260V/0.46A
Efficiency @220Vac	92.5%	94.5%		Output 260V/0.46A
Efficiency @277Vac	93.0%	95.0%		Output 260V/0.46A
O/P Current Tolerance	-5%		+5%	
O/P Current Ripple(PK-AV)		5%	10%	Full load
Start-up Current Overshoot			10%	Full load
Start-up Time			0.7S	230Vac, Full load
Line Regulation	-2%		+2%	Full load
Load Regulation	-6%		+6%	
Temperature Coefficient	-0.03%/°C		+0.03%/°C	$T_c: 0^{\circ}C \sim 90^{\circ}C$
OTP	90°C	100°C	110°C	Drop current when OTP, and it can be automatically restored after the abnormality is removed.
Short Circuit Protection				Driver will not be damaged, Shutdown after short circuit identification

SS-120NH-E260D LED DRIVER

Other Characteristics

Parameter	Min.	Typ.	Max.	Remark
DALI Dimming Level	1-170(10%)		254(100%)	Logarithmic dimming curves
DALI Dimming(Optional)	Meet DALI-2			lit. no afterglow
Lifetime(Tc≤75°C)	≥50,000 hours			
MTBF	201,000 hours			220Vac,Full load, Ta=25°C (MIL-HDBK-217F)
Tc	90°C			
Warranty	5 years			Tc 75°C
Net Weight	530g			
Dimension	185mm*52.5mm*34mm			L x Wx H

NOTE: All the parameters above are tested Ta 25°C and LED load, unless specified.

SS-120NH-E260D LED DRIVER

Environmental Requirements

Parameter	Min.	Typ.	Max.	Remark
Operating Temperature(Tcase)	-40°C	25°C	+90°C	
Storage Temperature	-40°C	25°C	+90°C	
Operation Humidity	10%RH		90%RH	
Storage Humidity	5%RH		95%RH	
Altitude	-65m		4000m	

Safety and EMI/EMS Standards

Certification	Standard	Status	Remark
DALI-2	IEC62386-101(2.0),102(2.0),207(2.0)	✓	
UL/cUL	UL8750		
TUV	EN 61347-2-13:2014/A1:2017 EN61347-1:2015 EN62493:2015	✓	
RCM	AS/NZS61347.2.13		
BIS	IS15885:2012 Part 2 Sec 13		
CCC	GB 19510.14-2009		
CE	EN 61347-2-13:2014 EN61347-1:2008+A1:2011+A2:2013	✓	

EMI/EMS	Criterion	Remark
Conduction Emission	EN IEC 55015:2019+A11:2020	
Radiation Emission	EN IEC 55015:2019+A11:2020	
Harmonic Current Emissions	IEC/EN 61000-3-2:2019+A1:2021	Class C
Surge	IEC/EN61000-4-5	DM: 6kV,CM: 6kV,Criterion B
Ring Wave	IEC/EN 61000-4-12	DM: 6kV,CM: 6kV,Criterion B

SS-120NH-E260D LED DRIVER

Safety Test Items


Safety Test	Technical Indicators		Remark
Insulation Requirements	UL Insulation Requirements	TUV Insulation Requirements	
Input-Case	/	2U+1000Vac	Basic insulation
Input-Dim	/	2U+1000Vac	Basic insulation
Dim-Case	/	2U+1000Vac	Basic insulation
Insulation Resistance	$\geq 10M\Omega$		Input-Dim, Test voltage: 500Vdc
Ground Resistance	$\leq 0.1\Omega$		25A/1min
Leakage Current	$\leq 0.75mA$		277Vac

NOTE:

1. SOSEN warrants the LED Driver itself complies with EMC standard. However, LED Driver's EMC should be re-checked when integrated into lighting systems due to unexpected interference of components.
2. Please short (ACL and ACN), (V+ and V-), (Dim+ and Dim - and Vaux+ and Vaux-)when Hi-pot test.

Performance Curves

Input Inrush Current




Vin	Ipeak	T(@10% of Ipeak)	T(@50% of Ipeak)
120Vac	60A	520uS	
220Vac	100A		220uS
277Vac	130A	480uS	


SS-120NH-E260D LED DRIVER

Performance Curves

Output Voltage Vs. Output Current(Dim/AOC Window)




Efficiency Vs. Output Voltage(Vin=120Vac)




SS-120NH-E260D LED DRIVER

Performance Curves

Efficiency Vs. Output Voltage (Vin=220Vac)




Efficiency Vs. Output Voltage(Vin=277Vac)




SS-120NH-E260D LED DRIVER

Performance Curves

Power Factor Vs. Output Power




THD Vs. Output Power




SS-120NH-E260D LED DRIVER

Performance Curves


Output Power Vs. Input Voltage




Output Power Vs. Case Temperature



Output Power Vs. Dimming




Lifetime Vs. Case Temperature



SS-120NH-E260D LED DRIVER

Performance Curves

Output Power Vs. Dimming



SS-120NH-E260D LED DRIVER

Mechanical Characteristic

The diagram shows a central blue box labeled "LED DRIVER". On the left, under the heading "INPUT", there are four terminals: ACL, ACN, a ground symbol, and AOC. On the right, under the heading "OUTPUT", there are four terminals: V+, V-, DA, and DA. The DA terminals are grouped under the label "DALI".


AC Input Cable(Exposed Length 300±10mm):
UL/EU model: 18AWG 105°C 600V O.D: 2.77mm,Black:ACL,White:ACN,Green:⊕

DC Output Cable(Exposed Length 300±10mm):
UL/EU model: 18AWG 105°C 300V O.D: 1.95mm,Red:V+ Black:V-

DALI Cable(Exposed Length 220±10mm):
UL/EU model: 22AWG 105°C 300V O.D: 1.52mm Purple DA, Pink: DA

Name Description	Standard Code	mm(In.)
Overall Length	L1	185(7.28)
Mounting Hole Length	L2	175.5(6.91)
Case Length	L3	167(6.57)
Case Width	W1	52.5(2.07)
Mounting Hole Width	W2	32(1.26)
Case Height	H	34(1.34)
TC Point Position	X	150(5.91)
TC Point Position	Y	13(0.51)

Note
1,Please follow the "LED Driver User Manual" obtained from SOSEN's official website for assembly.
2,AC Input Cable,DC O/P Cable,DALI Cable:
Tinned length of wire:10±2mm



SS-120NH-E260D LED DRIVER



Assembly Tips

1. Highly recommended to seal the adjustable hole with silicon glue(#704 preferred) after adjusting the Driver's output current. Avoid permanent damage to adjust the potentiometer with suitable strength.
2. Dimming or AUX Power tinned connectors should be capped if not used to avoid dimming or AUX Power parts damage from external signals.
3. In order to meet the requirements of the power derating and the maximum ambient temperature of 50°C, an auxiliary heat sink must be added. It is recommended that the heat sink has a heat dissipation area of 380cm² and volume of 115cm³. Thermal grease should be applied between LED driver and the auxiliary heat sink to ensure the bottom of housing is in close contact with the heat sink.
4. Safety space between aluminum base and LED coppers >5mm.
5. Safety space/coppers between LED+ and LED- >1.8mm.
6. Minimize the copper area on the aluminum PCB to reduce parasitic capacitance and leakage current.
7. It is recommended to design LED beads in parallel first and then in series.
8. When the driver shutdown by some protection, it can be restarted via AC power-on or by sending a command from the DALI master.
9. The insulation level of LED light panels should meet the reliability design requirements.
10. For other precautions, please refer to the "LED Driver User Manual".
11. SOSEN reserves the right of final interpretation of the above parameters.

Package

- Outside carton dimension: L×W×H =495mm×385mm×162mm;
- 16PCS/Carton;
- Net weight/Piece: 0.53kg;Gross weight/Carton: 10kg;
- Please refer to the product name, model number, manufacturer identification, QC PASS, manufacturing date on the package.

Transportation

Packaging is designed suitable for transportation by trucks, vessels and flights. The products should be avoided direct sunlight and rain, loaded/unloaded with caution.

Storage

The product storage meets the standard of the GB 3873—83.
Products should be rechecked if stored for over 1 year before assembly.

RoHS

Products comply with RoHS Directive (2011/65/EU) and amendment 2015/863/EU.

Revision History

Version	Description of Update	Updated Date	Remark
V00	Original Release	2023/01/10	
V01	Update Output Power Vs. Dimming Curve	2023/03/10	
V02	Update Assembly Tips	2023/05/22	
V03	Update Lifetime	2023/11/24	
V04	Updated dimensions	2025/04/22	